

HERSTELLERERKLÄRUNG

Projekt

Firma Adolf Würth GmbH & Co. KG
 Ansprechpartner Jochen Klingert
 Telefon +49 7940 15 1239
 E-Mail Jochen.Klingert@wuerth.com

Gewerk _____
 Einbauort _____

Produktbezeichnung WÜRTH Brandschutzfugenmasse Acryl Art. Nr. 0893 303 002
 Anwendung/ Beschreibung Abdichtungssystem für Decken- und Wandanschlussfugen mit geringer Dehnbelastung.

Menge/behandelte Fläche/Stückzahl _____

VOC Gehalt < 5g/l (less water)

Anforderungen	Erfüllt	Bemerkung
Chlorparaffine < 0,1%	ja	
TCEP < 0,1%	ja	
Formaldehyd < 10µg/m ³	ja	
frei von PBB, PBDE	ja	

Vorhandene Dokumente

Sicherheitsdatenblatt ja
 Prüfzeugnisse nein
 Sonstiges siehe Würth Online-Shop



Adolf Würth GmbH & Co. KG
 Reinhold-Würth-Str. 12 · 17
 74653 Künzelsau/Deutschland
 T +49 7940 15-0 · F +49 7940 15-1000
 info@wuerth.com · www.wuerth.de

09.11.2021
 Datum

 Unterschrift

DECLARATION OF PERFORMANCE

LE_0893303002_00_S_Brandschutzfugenmasse Acryl

1. Unique identification code of the product type:

acrylic fire-resistant joint sealer

Art. No. 0893303002

EN 15651-1:F-EXT-INT

2. Type, batch, or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

batch number: see packaging

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

**joint sealants for facade elements
EN 15651-1: F-EXT-INT**

4. Name, registered trade name, or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

**Adolf Würth GmbH & Co. KG
Reinhold-Würth-Str. 12-17
D-74653 Künzelsau**

5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):

Not relevant

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

**System 3
System 3 for testing fire behavior**

7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:

The notified body and test laboratory Ginger (0074) conducted the System 3 initial type tests and issued the test and classification reports.

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

Not relevant

9. Declared performance:

Conditioning: method A (in accordance with ISO 8339)

Base material: Mortar

Aluminum

Essential characteristics	Performance	Harmonized technical specification
Fire behavior	Class E	EN 15651-1:2012
Release of chemicals harmful to health and/or the environment	See safety data sheet	
Resistance to flow (EN ISO 7390)	≤ 3 mm	
Loss in volume (EN ISO 10563)	≤ 25%	
Adhesion/cohesion properties after immersion in water (EN ISO 10591)	≥ 100%	
Durability (ISO 8339, ISO 9046, ISO 10591)	passed	

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies:

Not relevant

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:



Marcel Strobel
(Head of Product Management)
Künzelsau, 3/1/2014



Dr.-Ing. Siegfried Beichter
(Head of Quality, Authorized Signatory)